

Wes Vice Hardwoods
& Supply Inc.
Nederland, Texas



Panel
Mouldings

SPECIFICATIONS



MOULDING # PA 1

CUSTOMER: _____

COMMENTS: 20 * HOOK

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # PA 2

CUSTOMER: _____


COMMENTS: 20 * HOOK

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE



OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 3**


CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



**MUST USE HOLD UP AFTER LAST BOTTOM
HEAD CUTS RABBIT**



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 4**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 5**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 6**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 7**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 8**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 9**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 10**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 11**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 12**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 13**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS

MOULDING # **PA 14**



CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR

VARIABLE TILT RABBIT



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 15**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 16**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 17**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PA 18**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # PA 19

CUSTOMER: _____

COMMENTS: 20 * HOOK

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS

MOULDING # PA 20


CUSTOMER: _____

COMMENTS: 20* HOOK

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR

5/14 x 1 1/2



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS

MOULDING # **PA 21**

CUSTOMER: _____


COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR

\$45
set up

INSIDE OF MACHINE



OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 22**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 23**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PA 24**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 1**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 2**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS

MOULDING # PL 3

CUSTOMER: _____


COMMENTS: 20 * HOOK

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR

INSIDE OF MACHINE

OUTFEED VIEW COMING



SPECIFICATIONS


MOULDING # PL 4

CUSTOMER: _____

COMMENTS: 20* HOOK

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 5**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 6**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # PL 7

CUSTOMER: _____

COMMENTS: 20* HOOK

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 8**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS

MOULDING # **PL 9**


CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR

INSIDE OF MACHINE



OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 10**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS



MOULDING # **PL 10 DBL**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR

**CAUTION: KICK BACK HAZARD
MAY CAUSE INJURY OR DEATH
MUST USE OSHA APPROVED
ANTI-KICKBACK DEVICE**



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 11**

CUSTOMER: _____

COMMENTS: **20° HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 12**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 13**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 14**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



NOTE: MAKE SYMMETRICAL

INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS

MOULDING # **PL 15 DBL**


CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS


T-REX LONG WEAR

**CAUTION: KICK BACK HAZARD
MAY CAUSE INJURY OR DEATH
MUST USE OSHA APPROVED
ANTI-KICKBACK DEVICE**



KNIFE EXTENDS .010 INTO
ONION SKIN

DOUBLE SHIM LAST BOTTOM
STRAIGHT KNIVES TO REMOVE
.040 ONION SKIN



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 16**

CUSTOMER: _____

COMMENTS: **20° HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR

INSIDE OF MACHINE



FEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 17**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 18**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 19**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 20**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS



MOULDING # **PL 20 A**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



OUTFEED VIEW COMING



SPECIFICATIONS

MOULDING # **PL 20 B**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 21**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **PL 22**

CUSTOMER: _____

COMMENTS: **20 * HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **PL 23**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING

SPECIFICATIONS


MOULDING # **DR STP 1**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS

T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # **TS-CH 40**

CUSTOMER: _____

COMMENTS: **20* HOOK**

MOULDER: 5/16 T-REX CORR., 1.5 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING


SPECIFICATIONS

MOULDING # CH 2

CUSTOMER:

COMMENTS: 20 * HOOK

MOULDER: 5/16 T-REX CORR., 1.375 START DEPTH, 10MM AXIALS
T-REX LONG WEAR



INSIDE OF MACHINE

OUTFEED VIEW COMING